

Demtac

Performance and use

The concrete form oils **DEMTAC** are a special mixture of mineral oils and special additives. They allow the removal of steel forms and insure a smooth finish. They are characterised by the following properties:

- makes the removal easier;
- insures a smooth finish of the concrete;
- protects the forms from the corrosion and rot;
- excellent adherence to the metal;
- increases the durability of the forms.

It is possible to dilute the **DEMTAC 22** or **46** with kerosene to facilitate the application.

A preliminary test with 10% of kerosene is recommended. The results of this test will indicate if less or more oil is needed to obtain the required viscosity.

The **DEMTAC 5** is an oil of low viscosity ready to use. All **DEMTAC** oils truly possess a lot of advantages for concrete molding.

Specifications

	DEMTAC 5	DEMTAC 10	DEMTAC 22	DEMTAC 22D	DEMTAC 32	DEMTAC 46
Density (kg/m ³ @ 15°C)	838	855	872	878	874	876
Viscosity cSt @ 40 °C	5,8	10,9	20,5	22,5	31,3	46,9
Viscosity cSt @ 100 °C	--	2,6	4,2	4,5	5,6	6,5
Pour Point (°C)	-27	-27	-24	-24	-23	-18
Flash Point (°C)	104	160	162	164	188	210
Color, Max.	1,5	1,0	1,0	1,5	1,5	1,5

Available formats

	20 L	205L	BULK	TOTE
DEMTAC 5	28-6273-10	28-6273-05	28-6273-00	
DEMTAC 10		28-6274-05	28-6274-00	
DEMTAC 22		28-6275-05	28-6275-00	
DEMTAC 22 DOUBLE	28-6284-10	28-6284-05	28-6284-00	
DEMTAC 46			28-2627-00	28-2627-04