# SAFETY DATA SHEET





# 1. Identification

	1. Iden	tification	
Product identifier	NG-X 10W-40		
Other means of identification	0163 (Med Ash), 0169 (Low A	sh)	
Recommended use	Natural gas engine oil		
Recommended restrictions	Not for food, drug, or household use.		
Manufacturer/Importer/Supplier	/Distributor information		
Manufacturer			
Company name	Nemco Resources Ltd		
Address	25 Midland Street		
	Winnipeg, MB R3E 3J6 Canada		
Telephone	-	04-788-1030	
•		04-788-1593	
		55-755-6737 (M-F 8am-4:30pm)	
Website E-mail	www.nemco.ca/msds-safety-ir info@nemco.ca	Iormation	
Emergency phone number	-	55-755-6737 (M-F 8am-4:30pm)	
Supplier	See above.	( I )	
	2 Hazard i	dentification	
Physical hazards	Not classified.		
Health hazards	Carcinogenicity	Category 1B	
Environmental hazards	Not classified.		
Signal word	Danger		
Hazard statement	May cause cancer.		
Precautionary statement	-		
Prevention		ore use. Do not handle until all sa ve gloves, protective clothing, eye	
Response	IF exposed or concerned: Get	medical attention.	
Storage	Store locked up.		
Disposal	Dispose of container in accord	ance with local, regional, national	and international regulations.
Other hazards	None known.		
Supplemental information	None.		
	3. Composition/infor	mation on ingredients	
Mixtures			
Chemical name	Common name and syn	onyms CAS num	ber %
Distillates (petroleum), hydrotre heavy paraffinic		64742-54	
Distillates (petroleum), solvent-dewaxed heavy paraffi	n	64742-65	5-0 1-5
All concentrations are in percent b	y weight unless ingredient is a g	as. Gas concentrations are in per	cent by volume.
Composition comments		centage (concentration) of compo	
4. First-aid measures			
Inhalation	If symptoms develop move vic	tim to fresh air. If symptoms persis	st, obtain medical attention.

Skin contact	Flush with cool water. Wash with soa		
Eye contact	Flush with cool water. Remove contact attention if irritation persists.	ct lenses, if applicable, and conti	nue flushing. Obtain medica
Ingestion	Rinse mouth. Do not induce vomiting reduce risk of aspiration. Never give a Obtain medical attention.		
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause to	emporary irritation.	
Indication of immediate medical attention and special treatment needed	Provide general supportive measures	and treat symptomatically. Sym	ptoms may be delayed.
General information	IF exposed or concerned: Get medica label where possible). Show this safe eyes and skin. Keep out of reach of c	ty data sheet to the doctor in atte	
	5. Fire-fighting m	easures	
Suitable extinguishing media	Water fog. Foam. Dry chemical powd	er. Carbon dioxide.	
Unsuitable extinguishing media	Do not use water jet as an extinguish		
Specific hazards arising from the chemical	During fire, gases hazardous to healt	n may be formed.	
Hazardous combustion products	May include and are not limited to: O	kides of carbon.	
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus a	nd full protective clothing must b	e worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.		
Specific methods	Use standard firefighting procedures	and consider the hazards of othe	er involved materials.
General fire hazards	No unusual fire or explosion hazards	noted.	
	6. Accidental release	e measures	
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. damaged containers or spilled materi adequate ventilation. Local authorities contained. For personal protection, se	al unless wearing appropriate pr s should be advised if significant	otective clothing. Ensure
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material possible. Absorb in vermiculite, dry sa recovery, flush area with water.	, if this is without risk. Dike the s	
	Small Spills: Wipe up with absorbent remove residual contamination.	material (e.g. cloth, fleece). Clea	in surface thoroughly to
	Never return spills to original containe containers. For waste disposal, see s		table, covered, labeled
Environmental precautions	Avoid discharge into drains, water co streams, ponds or public waters.	urses or onto the ground. Do not	discharge into lakes,
	7. Handling and	storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with eyes. Avoid prolonged exposure. Provide adequate ventilation Wear appropriate personal protective equipment. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material. When using do not eat or drink.		
Conditions for safe storage, including any incompatibilities	Store locked up. Store in tightly close Section 10 of the SDS). Keep out of r		compatible materials (see
	8. Exposure controls/Per	sonal protection	
Occupational exposure limits US. ACGIH Threshold Limit			-
Components	Туре	Value	Form

Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.

US. ACGIH Threshold Limit Values Components	Туре	Value	Form
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.
Canada. Alberta OELs (Occupational Hea Components	lth & Safety Code, Schedule 1, Tab Type	le 2) Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Canada. British Columbia OELs. (Occupa Safety Regulation 296/97, as amended)	tional Exposure Limits for Chemic	al Substances, Occ	-
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	1 mg/m3	Mist.
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	TWA	1 mg/m3	Mist.
Canada. Manitoba OELs (Reg. 217/2006, 1 Components	The Workplace Safety And Health A Type	Act) Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.
Canada. New Brunswick Regulation 91-19			-
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	STEL	10 mg/m3	Mist.
•	TWA	5 mg/m3	Mist.
Canada. Ontario OELs. (Control of Expos Components	ure to Biological or Chemical Ager Type	nts) Value	Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
Canada. Quebec OELs. (Ministry of Labor Components	<ul> <li>Regulation respecting occupation</li> <li>Type</li> </ul>	onal health and safe Value	ety) Form
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Components	Туре	Value
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	15 minute	10 mg/m3
	8 hour	5 mg/m3
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	15 minute	10 mg/m3
	8 hour	5 mg/m3
ological limit values	No biological exposure limits noted for	the ingredient(s).
opropriate engineering ontrols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.	
dividual protection measures	s, such as personal protective equipme	nt
Eye/face protection	Wear safety glasses with side shields	(or goggles).
Skin protection		
Hand protection	Impervious gloves. Confirm with reputable supplier first.	
Other	Wear appropriate chemical resistant clothing. As required by employer code.	
Respiratory protection	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).	
Thermal hazards	Not applicable.	
eneral hygiene onsiderations		e measures, such as washing after handling the material oking. Routinely wash work clothing and protective /hen using do not eat or drink.

9. Physical and chemical properties		
Annoaranaa	Liquid	
Appearance Physical state	Liquid.	
Form	Liquid.	
	Amber	
Colour		
Odour	Mild petroleum	
Odour threshold	Not available.	
рН	Not available.	
Melting point/freezing point	Not available.	
Initial boiling point and boiling range	Not available.	
Flash point	> 205.0 °C (> 401.0 °F) Closed cup	
Evaporation rate	<1 (Butyl acetate = 1)	
Flammability (solid, gas)	Not applicable.	
Upper/lower flammability or exp	losive limits	
Flammability limit - lower (%)	Not available.	
Flammability limit - upper (%)	Not available.	
Explosive limit - lower ( %)	Not available.	
Explosive limit – upper (%)	Not available.	
Vapour pressure	Not available.	
Vapour density	Not available.	
Relative density	0.87-0.89	
Solubility(ies)		
Solubility (water)	Insoluble	
Partition coefficient (n-octanol/water)	Not available.	

Auto-ignition temperature	> 260 °C (> 500 °F)		
Decomposition temperature	Not available.		
Viscosity	Not available.		
Other information			
Explosive properties	Not explosive.		
Kinematic viscosity	103 cSt		
Oxidising properties	Not oxidising.		
	10. Stability and re	eactivity	
Reactivity	The product is stable and non-reactive	under normal conditions of use, storage and transport.	
Chemical stability	Material is stable under normal condition	ons.	
Possibility of hazardous reactions	No dangerous reaction known under c	onditions of normal use.	
Conditions to avoid	Do not mix with other chemicals.		
Incompatible materials	Strong oxidising agents.		
Hazardous decomposition products	May include and are not limited to: Oxi	des of carbon.	
	11. Toxicological inf	formation	
Information on likely routes of	exposure		
Inhalation	Prolonged inhalation may be harmful.		
Skin contact	No adverse effects due to skin contact	are expected.	
Eye contact	Direct contact with eyes may cause ter	mporary irritation.	
Ingestion	May cause stomach distress, nausea o		
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.		
Information on toxicological ef	facts		
Acute toxicity	See below.		
Acute toxicity	Occ below.		
-	Spacios	Tost Posults	
Components	Species	Test Results	
Components Distillates (petroleum), hydrotreat	<b>Species</b> ted heavy paraffinic (CAS 64742-54-7)	Test Results	
Components Distillates (petroleum), hydrotreat Acute	•	Test Results	
Components Distillates (petroleum), hydrotreat	•		
Components Distillates (petroleum), hydrotreat Acute Dermal	ted heavy paraffinic (CAS 64742-54-7)	Test Results > 5000 mg/kg, 24 Hours, ECHA	
Components Distillates (petroleum), hydrotreat Acute Dermal LD50	ted heavy paraffinic (CAS 64742-54-7)		
Components Distillates (petroleum), hydrotreat Acute Dermal LD50 Inhalation	ted heavy paraffinic (CAS 64742-54-7) Rabbit	> 5000 mg/kg, 24 Hours, ECHA	
Components Distillates (petroleum), hydrotreat Acute Dermal LD50 Inhalation LC50	ted heavy paraffinic (CAS 64742-54-7) Rabbit	> 5000 mg/kg, 24 Hours, ECHA	
Components Distillates (petroleum), hydrotreat Acute Dermal LD50 Inhalation LC50 Oral LD50	ted heavy paraffinic (CAS 64742-54-7) Rabbit Rat	> 5000 mg/kg, 24 Hours, ECHA > 5.2 mg/L, 4 Hours, ECHA	
Components Distillates (petroleum), hydrotreat Acute Dermal LD50 Inhalation LC50 Oral LD50	ted heavy paraffinic (CAS 64742-54-7) Rabbit Rat Rat	> 5000 mg/kg, 24 Hours, ECHA > 5.2 mg/L, 4 Hours, ECHA	
Components Distillates (petroleum), hydrotreat Acute Dermal LD50 Inhalation LC50 Oral LD50 Distillates (petroleum), solvent-de	ted heavy paraffinic (CAS 64742-54-7) Rabbit Rat Rat	> 5000 mg/kg, 24 Hours, ECHA > 5.2 mg/L, 4 Hours, ECHA	
Components Distillates (petroleum), hydrotreat Acute Dermal LD50 Inhalation LC50 Oral LD50 Distillates (petroleum), solvent-de Acute	ted heavy paraffinic (CAS 64742-54-7) Rabbit Rat Rat	> 5000 mg/kg, 24 Hours, ECHA > 5.2 mg/L, 4 Hours, ECHA	
Components Distillates (petroleum), hydrotreat Acute Dermal LD50 Inhalation LC50 Oral LD50 Distillates (petroleum), solvent-de Acute Dermal	ted heavy paraffinic (CAS 64742-54-7) Rabbit Rat Rat ewaxed heavy paraffin (CAS 64742-65-0)	<ul> <li>&gt; 5000 mg/kg, 24 Hours, ECHA</li> <li>&gt; 5.2 mg/L, 4 Hours, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> </ul>	
Components Distillates (petroleum), hydrotreat Acute Dermal LD50 Inhalation LC50 Oral LD50 Distillates (petroleum), solvent-de Acute Dermal LD50	ted heavy paraffinic (CAS 64742-54-7) Rabbit Rat Rat ewaxed heavy paraffin (CAS 64742-65-0)	<ul> <li>&gt; 5000 mg/kg, 24 Hours, ECHA</li> <li>&gt; 5.2 mg/L, 4 Hours, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> </ul>	
Components Distillates (petroleum), hydrotreat Acute Dermal LD50 Inhalation LC50 Oral LD50 Distillates (petroleum), solvent-de Acute Dermal LD50 Inhalation	ted heavy paraffinic (CAS 64742-54-7) Rabbit Rat Rat ewaxed heavy paraffin (CAS 64742-65-0) Rabbit	<ul> <li>&gt; 5000 mg/kg, 24 Hours, ECHA</li> <li>&gt; 5.2 mg/L, 4 Hours, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> <li>&gt; 2000 mg/kg, 24 Hours, ECHA</li> <li>2.2 mg/L, 4 Hours, ECHA</li> </ul>	
Components Distillates (petroleum), hydrotreat Acute Dermal LD50 Inhalation LC50 Oral LD50 Distillates (petroleum), solvent-de Acute Dermal LD50 Inhalation LC50	ted heavy paraffinic (CAS 64742-54-7) Rabbit Rat Rat ewaxed heavy paraffin (CAS 64742-65-0) Rabbit	<ul> <li>&gt; 5000 mg/kg, 24 Hours, ECHA</li> <li>&gt; 5.2 mg/L, 4 Hours, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> <li>&gt; 2000 mg/kg, 24 Hours, ECHA</li> </ul>	
Components Distillates (petroleum), hydrotreat Acute Dermal LD50 Inhalation LC50 Oral LD50 Distillates (petroleum), solvent-det Acute Dermal LD50 Inhalation LC50 Oral LD50 Oral LD50 Oral LD50 Inhalation LD50 Inhalation LD50 Inhalation LD50	ted heavy paraffinic (CAS 64742-54-7) Rabbit Rat Rat ewaxed heavy paraffin (CAS 64742-65-0) Rabbit Rat	<ul> <li>&gt; 5000 mg/kg, 24 Hours, ECHA</li> <li>&gt; 5.2 mg/L, 4 Hours, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> <li>&gt; 2000 mg/kg, 24 Hours, ECHA</li> <li>2.2 mg/L, 4 Hours, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> </ul>	
Components Distillates (petroleum), hydrotreat Acute Dermal LD50 Inhalation LC50 Oral LD50 Distillates (petroleum), solvent-det Acute Dermal LD50 Inhalation LC50 Oral LD50 Oral LD50 Oral LD50 Inhalation LD50 Inhalation LD50 Inhalation LD50	ted heavy paraffinic (CAS 64742-54-7) Rabbit Rat Rat ewaxed heavy paraffin (CAS 64742-65-0) Rabbit Rat Rat	<ul> <li>&gt; 5000 mg/kg, 24 Hours, ECHA</li> <li>&gt; 5.2 mg/L, 4 Hours, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> <li>&gt; 2000 mg/kg, 24 Hours, ECHA</li> <li>2.2 mg/L, 4 Hours, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> </ul>	
Components Distillates (petroleum), hydrotreat Acute Dermal LD50 Inhalation LC50 Oral LD50 Distillates (petroleum), solvent-de Acute Dermal LD50 Inhalation LC50 Oral LD50 Skin corrosion/irritation	ted heavy paraffinic (CAS 64742-54-7) Rabbit Rat Rat ewaxed heavy paraffin (CAS 64742-65-0) Rabbit Rat Rat Rat Prolonged skin contact may cause tem	<ul> <li>&gt; 5000 mg/kg, 24 Hours, ECHA</li> <li>&gt; 5.2 mg/L, 4 Hours, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> <li>&gt; 2000 mg/kg, 24 Hours, ECHA</li> <li>2.2 mg/L, 4 Hours, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> </ul>	
Components Distillates (petroleum), hydrotreat Acute Dermal LD50 Inhalation LC50 Oral LD50 Distillates (petroleum), solvent-de Acute Dermal LD50 Inhalation LC50 Oral LD50 Skin corrosion/irritation Exposure minutes	ted heavy paraffinic (CAS 64742-54-7) Rabbit Rat Rat ewaxed heavy paraffin (CAS 64742-65-0) Rabbit Rat Rat Prolonged skin contact may cause terr Not available.	<ul> <li>&gt; 5000 mg/kg, 24 Hours, ECHA</li> <li>&gt; 5.2 mg/L, 4 Hours, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> <li>&gt; 2000 mg/kg, 24 Hours, ECHA</li> <li>2.2 mg/L, 4 Hours, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> </ul>	
Components Distillates (petroleum), hydrotreat Acute Dermal LD50 Inhalation LC50 Oral LD50 Distillates (petroleum), solvent-det Acute Dermal LD50 Inhalation LC50 Oral LD50 Skin corrosion/irritation Exposure minutes Erythema value	ted heavy paraffinic (CAS 64742-54-7) Rabbit Rat Rat ewaxed heavy paraffin (CAS 64742-65-0) Rabbit Rat Rat Prolonged skin contact may cause terr Not available. Not available.	<ul> <li>&gt; 5000 mg/kg, 24 Hours, ECHA</li> <li>&gt; 5.2 mg/L, 4 Hours, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> <li>&gt; 2000 mg/kg, 24 Hours, ECHA</li> <li>2.2 mg/L, 4 Hours, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> </ul>	
Components Distillates (petroleum), hydrotreat Acute Dermal LD50 Inhalation LC50 Oral LD50 Distillates (petroleum), solvent-de Acute Dermal LD50 Inhalation LC50 Oral LD50 Skin corrosion/irritation Exposure minutes Erythema value Oedema value Serious eye damage/eye	ted heavy paraffinic (CAS 64742-54-7) Rabbit Rat Rat ewaxed heavy paraffin (CAS 64742-65-0) Rabbit Rat Rat Prolonged skin contact may cause tem Not available. Not available. Not available.	<ul> <li>&gt; 5000 mg/kg, 24 Hours, ECHA</li> <li>&gt; 5.2 mg/L, 4 Hours, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> <li>&gt; 2000 mg/kg, 24 Hours, ECHA</li> <li>2.2 mg/L, 4 Hours, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> </ul>	
Components Distillates (petroleum), hydrotreat Acute Dermal LD50 Inhalation LC50 Oral LD50 Distillates (petroleum), solvent-de Acute Dermal LD50 Inhalation LC50 Oral LD50 Skin corrosion/irritation Exposure minutes Erythema value Oedema value Serious eye damage/eye irritation	ted heavy paraffinic (CAS 64742-54-7) Rabbit Rat Rat ewaxed heavy paraffin (CAS 64742-65-0) Rabbit Rat Rat Prolonged skin contact may cause tem Not available. Not available. Not available. Direct contact with eyes may cause ter	<ul> <li>&gt; 5000 mg/kg, 24 Hours, ECHA</li> <li>&gt; 5.2 mg/L, 4 Hours, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> <li>&gt; 2000 mg/kg, 24 Hours, ECHA</li> <li>2.2 mg/L, 4 Hours, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> </ul>	
Components Distillates (petroleum), hydrotreat Acute Dermal LD50 Inhalation LC50 Oral LD50 Distillates (petroleum), solvent-de Acute Dermal LD50 Inhalation LC50 Oral LD50 Skin corrosion/irritation Exposure minutes Erythema value Oedema value Serious eye damage/eye irritation Corneal opacity value	ted heavy paraffinic (CAS 64742-54-7) Rabbit Rat Rat ewaxed heavy paraffin (CAS 64742-65-0) Rabbit Rat Rat Rat Prolonged skin contact may cause tem Not available. Not available. Direct contact with eyes may cause tem Not available.	<ul> <li>&gt; 5000 mg/kg, 24 Hours, ECHA</li> <li>&gt; 5.2 mg/L, 4 Hours, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> <li>&gt; 2000 mg/kg, 24 Hours, ECHA</li> <li>2.2 mg/L, 4 Hours, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> <li>&gt; 5000 mg/kg, ECHA</li> </ul>	

	Nist susting the			
Conjunctival oedema value	Not available.			
Recover days	Not available.			
Respiratory or skin sensitisation	n			
<b>Respiratory sensitisation</b>	Not a respiratory sensitizer.			
Skin sensitisation	This product is not expected to cause skin sensitisation.			
Germ cell mutagenicity	No data available to indicate p mutagenic or genotoxic.	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	See below.			
Canada - Manitoba OELs: ca	arcinogenicity			
Distillates (petroleum), sc (CAS 64742-65-0)	olvent-dewaxed heavy paraffin	Suspected human carcinogen.		
IARC Monographs. Óverall	Evaluation of Carcinogenicity			
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)		Volume 33, Supplement 7 - 3 Not classifiable as to carcinogenicity to humans.		
Distillates (petroleum), so (CAS 64742-65-0)	olvent-dewaxed heavy paraffin	Volume 33, Supplement 7 - 3 Not classifiable as to carcinogenicity to humans.		
Reproductive toxicity	Not applicable.			
Specific target organ toxicity - single exposure	Not classified.			
Specific target organ toxicity - repeated exposure	Not applicable.			
Aspiration hazard	Not an aspiration hazard.			
Chronic effects	Not available.			
Further information	Not available.			
	12. Ecologio	cal information		
Ecotoxicity	See below			
Ecotoxicological data				

	Species	Test Results
ted heavy pa	raffinic (CAS 64742-54-7)	
EC50	Daphnia	1000 mg/L, 48 Hours
ewaxed heav	y paraffin (CAS 64742-65-0)	
EC50	Daphnia	1000 mg/L, 48 Hours
No data i	s available on the degradabil	ity of any ingredients in the mixture.
No data available.		
No data available.		
Not availa	able.	
		s (e.g. ozone depletion, photochemical ozone creation warming potential) are expected from this component.
	13. Disposal consid	lerations
		ed containers at licensed waste disposal site. Dispose o ional, national and international regulations.
	EC50 ewaxed heav EC50 No data a No data a No data a Not availa No other potential, Collect ar	ewaxed heavy paraffin (CAS 64742-65-0) EC50 Daphnia No data is available on the degradabili No data available. No data available. Not available. No other adverse environmental effect potential, endocrine disruption, global v <b>13. Disposal consid</b> Collect and reclaim or dispose in seale

Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

General

Canada: TDG Proof of Classification: Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.

### Transportation of Dangerous Goods (TDG - Canada)

Not regulated as dangerous goods.

## 15. Regulatory information

# Canadian federal regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR. Export Control List (CEPA 1999, Schedule 3) Not listed. Greenhouse Gases Not listed. Precursor Control Regulations Not regulated.

WHMIS status

Hazardous

#### International regulations

#### Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
*A "Yes" indicates that all con	ponents of this product comply with the inventory requirements administered b	by the governing country(s)

16. Other information

LEGEND	HEALTH * 2	
Severe4Serious3Moderate2Slight1Minimal0	FLAMMABILITY 0   PHYSICAL HAZARD 0   PERSONAL PROTECTION X	
Issue date Effective date Version No.	19-December-2022 19-December-2022 01	
Other information	For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.	
Disclaimer	The information in the safety data sheet was written by Dell Tech Laboratories Ltd. (www.delltech.com) based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.	
Prepared by	Dell Tech Laboratories Ltd. Phone: (519) 858-5021	